

# DISTRIBUTION CENTER WITH FIXED INPUT AND PHASE LOAD MEASUREMENT TSR 63/125A

## Fixed Connection 63A Floor Cabinet with Phase Meters

The **fixed connection 63A floor cabinet** is a reliable and efficient power distribution unit designed for construction sites and temporary electrical installations. Equipped with **phase meters**, the cabinet measures the **current and voltage** of each phase, ensuring accurate monitoring. Additionally, **indicator lights** signal when power is being supplied to the phases for easy status checking.

This **63A power distribution cabinet** supports a **125A chaining option** through its lower part, enabling seamless power distribution across multiple floors.

## Lightweight and Durable Construction

Crafted from **aluminium**, the **floor cabinet** is lightweight yet durable. Designed for **easy handling**, it features a **sturdy handle** for carrying and **hanging loops** for effortless wall mounting. The cabinet also comes with **stable legs**, allowing it to be placed securely on the floor.

## High-Quality European Components & Customization

Manufactured in **Finland**, this **temporary power distribution cabinet** is built using premium **European components** from **PCE** and **Schneider**, ensuring long-term reliability. Every part is available as a **spare part**, guaranteeing easy maintenance.

The **floor cabinet** can be customized to meet



**specific customer needs**, including modifications to the **number and size of outlets**.

- ✓ **63A distribution center** with phase meters
- ✓ **Indicator lights** for power status monitoring
- ✓ **125A chaining** for multi-floor power distribution
- ✓ **Lightweight aluminium construction**
- ✓ **Easy to carry, hang, or place on the floor**
- ✓ **Premium components from PCE & Schneider**
- ✓ **Made in Finland**
- ✓ **Customizable outlet configuration**

SKU: 5000334/2

## TECHNICAL ATTRIBUTES

<b>Nominal Current</b>	125 A	<b>Fuses</b>	1 x C16 3P 3 x C16 1P 2 x C32 3P
<b>Nominal voltage</b>	400 V	<b>Fixed input</b>	AL/CU 6-95mm <sup>2</sup>
<b>RCD</b>	1 x 40A/30mA, 2 x 63/300mA	<b>Main switch</b>	125A
<b>Weight</b>	17,8 kg	<b>Protection class</b>	IP44
<b>Measurements</b>	22x46x82 cm		
<b>Outlets</b>	1x63A, 3 x 32A, 1 x 16A, 2 x 16A 230V		

## ADDITIONAL PRODUCT DESCRIPTION

<https://youtu.be/Ek19dAKfKy0>

## OTHER PRODUCT IMAGES

