

## ESE 1006 SG-GT ES DUPLEX

11,0 / 10,0kVA ENDRESS DUPLEX Plus Line  
generator with electric start

SKU: E113160



### TECHNICAL ATTRIBUTES

|  |  |   |           |
|--|--|---|-----------|
| <b>Modell</b>                            |  | <b>Nominal current A</b>                        | 43,5 A    |
| <b>Measurements L x W<br/>x H mm</b>     | 850 x 650 x 575 mm   | <b>Fuel</b>                                     | Bensiini  |
| <b>Weight (kg) ~</b>                     | 162kg  | <b>Garden tools up to</b>                       | 6000 W    |
| <b>Running time at 75%<br/>load (h)</b>  | 9h   | <b>Protection class</b>                         | 54 IP     |
| <b>Shockproof sockets</b>                | 2 x 230 V/16 A 1 x<br>CEE 230 V/16 A 1 x<br>CEE 230 V/32 A | <b>Fuel tank capacity [l]</b>                   | 30l       |
| <b>Continuous power</b>                  | 10,0 / 9,0 kVA/kW  | <b>Frequency Hz</b>                             | 50 Hz     |
| <b>Kompressorit ja<br/>pumput enint.</b> | 4500 W   | <b>Power 3000 r/min speed kW</b>                | 12,5 kW   |
| <b>Fuel cons. at 75%<br/>PRP [L/h]</b>   | 3,2l   | <b>Power factor (Cos theta)</b>                 | 0,9 cos φ |
| <b>Volume</b>                            | 653 cm <sup>3</sup>  | <b>Alternator model</b>                         |           |
| <b>Start-up system</b>                   | Akkuavusteinen<br>sähkökäynnistin                          | <b>Sound pressure level LPA (7m)<br/>db (A)</b> | 67 db(A)  |
| <b>Possible<br/>applications</b>         | 230 V  | <b>Sound pressure level LPA<br/>db(A)</b>       | 97 db(A)  |
|  |  | <b>Electric tools up to</b>                     | 8900 W    |
|  |  | <b>Electric devices up to</b>                   | 9000 W    |

|  |                                 |                            |          |
|--|---------------------------------|----------------------------|----------|
| <b>Max. Output [LTP]<br/>kVA/kW</b>        | 11,0 / 9,9 kVA/kW               | <b>Welding tools up to</b> | 4,5 mm ø |
| <b>No. of motor<br/>cylinders and type</b> | Kaksisynterinen<br>nelitahtinen |                            |          |
| <b>Nominal voltage V</b>                   | 230 V                           |                            |          |