

ESE 1204 DHS-GT ES ISO DI

15,8 / 11,0kVA ENDRESS DIESEL SILENT LINE generator with electric start

SKU: E122005



TECHNICAL ATTRIBUTES

Model	HATZ 2G 40	Nominal voltage V	400 V
Measurements L x W x H mm	1270 x 610 x 920 mm	Nominal current A	15,9 A
Weight (kg) ~	275kg	Fuel	Diesel
Running time at 75% load (h)	7,5h	Protection class	23 IP
Shockproof sockets	1 x CEE 230V/16 A 1 x CEE 230V/32 A 1 x CEE 400V/16 A	Fuel tank capacity [l]	17l
Continuous power	11,0 / 8,8 kVA/kW	Frequency Hz	50 Hz
Kompressorit ja pumput enint.	4400 W	Power 3000 r/min speed kW	14,7 kW
Fuel cons. at 75% PRP [L/h]	2,3l	Power factor (Cos theta)	0,8 cos φ
Volume	997 cm ³	Alternator model	Duplex
Start-up system	E-Start incl. Battery	Sound pressure level LPA (7m) db (A)	72 db(A)
Possible applications	400 V	Sound pressure level LPA db(A)	97 db(A)
Max. Output [LTP] kVA/kW	15,8 / 12,6 kVA/kW	Electric devices up to	8700 W
No. of motor cylinders and type	2-cylinder 4 - stroke	Työmaa- ja puutarhatyökalut (asti)	5800 W
		Welding tools up to	4,5 mm ø

