

## ESE 1306 DHG-GT ES ISO DUPLEX

12,2/11,0 kVA ENDRESS DUPLEXplus Line -  
generator

SKU: E113258I



### TECHNICAL ATTRIBUTES

<b>Model</b>	HONDA GX 690 / 22 HP	<b>Possible applications</b>	400V
<b>Measurements L x W x H mm</b>	870 x 580 x 565	<b>No. of motor cylinders and type</b>	2-Sylinteri 4- Tahti OHV
<b>Weight (kg) ~</b>	165	<b>Nominal voltage V</b>	400/230
<b>Elektroniset kuluttajat enint</b>	9600W	<b>Nominal current A</b>	15.8/30.4
<b>Alternator type</b>	DUPLEX	<b>Fuel</b>	Bensiini
<b>Invertterihitsauskoneet enint</b>	6,5mm	<b>Puutarha- tai rakennuskoneet enint</b>	6400W
<b>Sockets</b>	2 x 230 V/16 A1 x CEE 400 V/16 A1 x CEE 400 V/32 A	<b>Engine build</b>	0.8
<b>Displacement [cm3]</b>	688	<b>Max. output 1~ [kVA/kW]</b>	7.7/7.0
<b>Jatkuva teho 1~ kVA/kW</b>	7.0/6.3	<b>Max. output 3~ [kVA/kW]</b>	12.2/9.8
<b>Jatkuva teho 3~ kVA/kW</b>	7.0/6.3	<b>Power tools up to</b>	9500W
<b>Kompressorit ja pumput enint.</b>	4800W	<b>Fuel tank capacity [l]</b>	20
		<b>Frequency Hz</b>	50
		<b>Power 3000 r/min speed kW</b>	13.2

<b>Kotelointiluokka generaattori IP</b>	54	<b>Power factor (Cos theta)</b>	0.8
<b>Fuel cons. at 75% PRP [L/h]</b>	5.2	<b>Sound pressure level LPA db(A)</b>	97
<b>Start-up system</b>	Sähkökäynnistys ja akku		