

ESE 1408 DLG ES DI DUPLEX SILENT

15,4 / 14,0kVA ENDRESS DUPLEX Silent Line
Diesel generator with electric start

SKU: E113032



TECHNICAL ATTRIBUTES

Modell		Nominal current A	20,2 A
Measurements L x W x H mm	1100 x 700 x 870 mm	Fuel	Diesel
Weight (kg) ~	320kg	Garden tools up to	7500 W
Running time at 75% load (h)	11,5h	Protection class	54 IP
Shockproof sockets	3 x 230 V/16 A 1 x CEE 400 V/16 A 1 X CEE 230 V/32 A	Fuel tank capacity [l]	35l
Continuous power	14,0 / 11,2 kVA/kW	Frequency Hz	50 Hz
Kompressorit ja pumpun enint.	5600 W	Power 3000 r/min speed kW	13,8 kW
Fuel cons. at 75% PRP [L/h]	3,0l	Power factor (Cos theta)	0,8 cos φ
Volume	954 cm ³	Alternator model	
Start-up system	Akkuavustein sähkökäynnistys	Sound pressure level LPA (7m) db (A)	71 db(A)
Possible applications	400 V	Sound pressure level LPA db(A)	96 db(A)
Max. Output [LTP] kVA/kW	15,4 / 12,3 kVA/kW	Electric tools up to	11300 W
		Electric devices up to	11400 W
		Welding tools up to	6,5 mm ø

**No. of motor
cylinders and type**

Kaksisylinterinen
nelitahtinen OHV

Nominal voltage V

400 V