

ESE 45 YW/RS

46,0/42,0kVA ENDRESS Rental Line RS 20 - 225
kVA -generator

SKU: E333274



TECHNICAL ATTRIBUTES

Model	Nelisynterinen nelitahtinen	No. of motor cylinders and type	4L
Measurements L x W x H mm	2300 x 950 x 1500 2300 x 950 x 1500	Engine output (LTP) kW	37,9kW
Weight (kg) ~	1129kg 1129	Nominal voltage V	400V 3~ /230V 1~ 400/230
Running time at 75% load (h)	24h	Nimellisvirta 3~ (PRP) A	60.6
Insulation	Class H	Nominal current / Cos theta	60,6 A 3~ /0,8
Alternator type	synkroni	Fuel	Diesel
Sockets	CEE 400V / 63A 1x CEE 400V / 32A 1x CEE 400V / 16A 1x CEE 230V / 16A 1x 230V / 16A Sukopistorasia 1x Klemmleiste	Main circuit breaker [Pole]	3
Displacement [cm³]	3319	Max. Output [LTP] [kVA/kw]	46,0/36,8
Jatkuva teho (PRP) kVA/kW	42.0/33.6	Continuous power [PRP] kVA / kW 3 ~	42,0 / 33,6 kVA/kW
Cooling system	vesijäähdytteinen	Fuel tank capacity [l]	200 Diesel / 200
Revolutions per minute (rpm) / control	1500/ mekaaninen	Frequency Hz	50
		Power factor (Cos theta)	0.8

Fuel cons. at 75% PRP [L/h]	8.19 8,2l	Alternator model	Synkroni MeccAlte
Volume	3319 cm ³	Sound pressure level LPA (7m) db (A)	66 db(A)
Start-up system	Sähkökäynnistin	Sound pressure level LPA db(A)	91 db(A) 91
Start-up system/Battery	Sähkökäynnistin /12V	Frequency / regulation	50 Hz / elektroninen
Max. Output [LTP] kVA / kW 3 ~	46,0 / 36,8 kVA/kW		