

## ESE 506 HG-GT DUPLEX

5,5 / 5,0kVA ENDRESS DUPLEX Plus Line generator

SKU: E113554



### TECHNICAL ATTRIBUTES

|                                      |                                   |   |          |
|--------------------------------------|-----------------------------------|---|----------|
| <b>Model</b>                         | Honda GX 390                      | <b>Nominal current A</b>                    | 21,7 A   |
| <b>Measurements L x W x H mm</b>     | 780 x 550 x 595 mm                | <b>Fuel</b>                                 | Bensiini |
| <b>Weight (kg) ~</b>                 | 102kg                             | <b>Garden tools up to</b>                   | 3300 W   |
| <b>Running time at 75% load (h)</b>  | 15h                               | <b>Protection class</b>                     | 54 IP    |
| <b>Shockproof sockets</b>            | 2 x 230 V/16 A 1 x CEE 230 V/32 A | <b>Fuel tank capacity [l]</b>               | 33l      |
| <b>Continuous power</b>              | 5,0 / 5,0 kVA/kW                  | <b>Frequency Hz</b>                         | 50 Hz    |
| <b>Kompressorit ja pumput enint.</b> | 2500 W                            | <b>Power 3000 r/min speed kW</b>            | 4,6 kW   |
| <b>Fuel cons. at 75% PRP [L/h]</b>   | 2,2l                              | <b>Power factor (Cos theta)</b>             | 1 cos φ  |
| <b>Volume</b>                        | 389 cm <sup>3</sup>               | <b>Alternator model</b>                     | Duplex   |
| <b>Start-up system</b>               | Narukäynnistin                    | <b>Sound pressure level LPA (7m) db (A)</b> | 60 db(A) |
| <b>Possible applications</b>         | 230 V                             | <b>Sound pressure level LPA db(A)</b>       | 97 db(A) |
| <b>Max. Output [LTP] kVA/kW</b>      | 5,5 / 5,5 kVA/kW                  | <b>Electric tools up to</b>                 | 4900 W   |
|                                      |                                   | <b>Electric devices up to</b>               | 5000 W   |
|                                      |                                   | <b>Welding tools up to</b>                  | 2,5 mm ø |

**No. of motor  
cylinders and type**

Yksisylinterinen  
nelitahtinen

**Nominal voltage V**

230 V