

ESE 506 HG-GT ISO DUPLEX

5,5/5,0 kVA ENDRESS DUPLEXplus Line -generator

SKU: E113554I



TECHNICAL ATTRIBUTES

Model	HONDA GX390 / 11 HP	Possible applications	230V
Measurements L x W x H mm	780 x 550 x 595	No. of motor cylinders and type	1-Sylinteri 4- Tahti OHV
Weight (kg) ~	102	Nominal voltage V	230
Running time at 75% load (h)	15.7	Nominal current A	21.7
Elektroniset kuluttajat enint	5000W	Fuel	Bensiini
Alternator type	DUPLEX	Puutarha- tai rakennuskoneet enint	3300W
Invertterihitsauskoneet enint	2,5mm	Engine build	1
Sockets	2 x 230 V/16 A1 x CEE 230 V/32 A	Max. output 1~ [kVA/kW]	5.5/5.5
Displacement [cm3]	389	Power tools up to	4900W
Jatkuva teho 1~ kVA/kW	5.0/5.0	Fuel tank capacity [l]	33
Jatkuva teho 3~ kVA/kW	5.0/5.0	Frequency Hz	50
Kompressorit ja pumput enint.	2500W	Power 3000 r/min speed kW	6.4
		Power factor (Cos theta)	1

Kotelointiluokka generaattori IP	54	Sound pressure level LPA (7m) db (A)	72
Fuel cons. at 75% PRP [L/h]	2.1	Sound pressure level LPA db(A)	97
Start-up system	Vetokäynnisteinen		