

## ESE 606 DHS-GT ES

8,3/7,0 kVA ENDRESS Professional GT -line generator

SKU: E112308



### TECHNICAL ATTRIBUTES

<b>Model</b>	HONDA GX390 / 11 HP	<b>No. of motor cylinders and type</b>	1-Sylinteri 4-Tahti OHV
<b>Measurements L x W x H mm</b>	800 x 538 x 576	<b>Nominal voltage V</b>	400/230
<b>Weight (kg) ~</b>	86	<b>Nominal current A</b>	10.1
<b>Running time at 75% load (h)</b>	14.3	<b>Fuel</b>	Bensiini
<b>Elektroniset kuluttajat enint</b>	5500W	<b>Puutarha- tai rakennuskoneet enint</b>	2800W
<b>Alternator type</b>	Synkroni	<b>Engine build</b>	0,8/0,9
<b>Invertterihitsauskoneet enint</b>	3,25mm	<b>Max. output 1~ [kVA/kW]</b>	4.9/4.4
<b>Sockets</b>	1 x 230 V/16 A, 1 x CEE 230 V/16 A, 1 x CEE 400 V/16 A	<b>Max. output 3~ [kVA/kW]</b>	8,3/6,6
<b>Displacement [cm3]</b>	389	<b>Power tools up to</b>	3700W
<b>Jatkuva teho 1~ kVA/kW</b>	3.5/3.2	<b>Fuel tank capacity [l]</b>	30
<b>Jatkuva teho 3~ kVA/kW</b>	3.5/3.2	<b>Frequency Hz</b>	50
<b>Kotelointiluokka generaattori IP</b>	23	<b>Power 3000 r/min speed kW</b>	6.4
<b>Fuel cons. at 75% PRP [L/h]</b>	2.1	<b>Power factor (Cos theta)</b>	0,8/0,9
		<b>Sound pressure level LPA (7m) db (A)</b>	72

<b>Start-up system</b>	Sähkökäynnistys ja akku	<b>Sound pressure level LPA db(A)</b>	97
<b>Possible applications</b>	400V		