

ESE 606 YS-GT ES ISO DI

6,0 / 4,9kVA ENDRESS DIESEL Silent Line
generator with electric start

SKU: E122009



TECHNICAL ATTRIBUTES

Model	YANMAR L 100	Nominal voltage V	230 V
Measurements L x W x H mm	945 x 595 x 825 mm	Nominal current A	21,3 A
Weight (kg) ~	186kg	Fuel	Diesel
Running time at 75% load (h)	18,5h	Protection class	23 IP
Shockproof sockets	1 x 230 V/16 A 1 x CEE 230 V/16 A 1 X CEE 230 V/32 A	Fuel tank capacity [l]	24l
Continuous power	4,9 / 4,4 kVA/kW	Frequency Hz	50 Hz
Kompressorit ja pumput enint.	2200 W	Power 3000 r/min speed kW	5,7 kW
Fuel cons. at 75% PRP [L/h]	1,3l	Power factor (Cos theta)	0,9 cos φ
Volume	435 cm ³	Alternator model	Duplex
Start-up system	Akkuavusteinen sähkökäynnistys	Sound pressure level LPA (7m) db (A)	68 db(A)
Possible applications	230 V	Sound pressure level LPA db(A)	93 db(A)
Max. Output [LTP] kVA/kW	6,0 / 5,4 kVA/kW	Electric devices up to	4200 W
No. of motor cylinders and type	Yksisylinterinen nelitahtinen	Työmaa- ja puutarhatyökalut (asti)	2800 W