

ESE 906 DLS ES DI

10,3 / 8,8kVA ENDRESS DIESEL Line generator
with electric start

SKU: E121010



TECHNICAL ATTRIBUTES

Model	LOMBARDINI 25LD330	Nominal voltage V	400 V
Measurements L x W x H mm	960 x 641 x 667 mm	Nominal current A	12,7 A
Weight (kg) ~	160kg	Fuel	Diesel
Running time at 75% load (h)	12h	Protection class	23 IP
Shockproof sockets	1 x 230V/16 A 1 x CEE 400V/16 A	Fuel tank capacity [l]	24l
Continuous power	8,8 / 7,0 kVA/kW	Frequency Hz	50 Hz
Kompressorit ja pumput enint.	3500 W	Power 3000 r/min speed kW	11,2 kW
Fuel cons. at 75% PRP [L/h]	2,0l	Power factor (Cos theta)	0,9 cos φ
Volume	654 cm ³	Alternator model	Duplex
Start-up system	Akkuavusteinen sähkökäynnistys	Sound pressure level LPA (7m) db (A)	80 db(A)
Possible applications	400 V	Sound pressure level LPA db(A)	105 db(A)
Max. Output [LTP] kVA/kW	10,3 / 8,2 kVA/kW	Electric devices up to	6900 W
No. of motor cylinders and type	Kaksisylinterinen nelitahtinen	Työmaa- ja puutarhatyökalut (asti)	4700 W
		Welding tools up to	4,0 mm ø