

## ESE 1006 HG-GT ES DUPLEX

8,8 kVA ENDRESS DUPLEXplus Line -generator

SKU: E113260I



### TECHNICAL ATTRIBUTES

|                                             |                                                             |                                               |                             |
|---------------------------------------------|-------------------------------------------------------------|-----------------------------------------------|-----------------------------|
| <b>Model</b>                                | HONDA GX630 /<br>21 HP                                      | <b>No. of motor cylinders and<br/>type</b>    | 2-Sylinteri 4-<br>Tahti OHV |
| <b>Measurements L x W x<br/>H mm</b>        | 870 x 580 x 595                                             | <b>Nominal voltage V</b>                      | 230                         |
| <b>Weight (kg) ~</b>                        | 164                                                         | <b>Nominal current A</b>                      | 34.8                        |
| <b>Elektroniset kuluttajat<br/>enint</b>    | 7200W                                                       | <b>Fuel</b>                                   | Bensiini                    |
| <b>Alternator type</b>                      | DUPLEX                                                      | <b>Puutarha- tai<br/>rakennuskoneet enint</b> | 4800W                       |
| <b>Invertterihitsauskoneet<br/>enint</b>    | 4,5mm                                                       | <b>Engine build</b>                           | 0.9                         |
| <b>Sockets</b>                              | 2 x 230 V/16 A1<br>x CEE 230 V/16<br>A1 x CEE 230<br>V/32 A | <b>Max. output 1~ [kVA/kW]</b>                | 8,8/8,0                     |
| <b>Displacement [cm3]</b>                   | 688                                                         | <b>Power tools up to</b>                      | 7100W                       |
| <b>Kompressorit ja pumput<br/>enint.</b>    | 3600W                                                       | <b>Fuel tank capacity [l]</b>                 | 20                          |
| <b>Kotelointiluokka<br/>generaattori IP</b> | 54                                                          | <b>Frequency Hz</b>                           | 50                          |
| <b>Fuel cons. at 75% PRP<br/>[L/h]</b>      | 4.2                                                         | <b>Power 3000 r/min speed<br/>kW</b>          | 12.4                        |
|                                             |                                                             | <b>Power factor (Cos theta)</b>               | 0.9                         |

**Start-up system**Sähkökäynnistys  
ja akku**Sound pressure level LPA  
db(A)**

97

**Possible applications**

230V