

ESE 406 HG-GT ES DUPLEX

4,4 / 4,0kVA ENDRESS DUPLEX Plus Line
generator with electric start

SKU: E113553



TECHNICAL ATTRIBUTES

Model	Honda GX 270	Nominal current A	17,4 A
Measurements L x W x H mm	780 x 550 x 595 mm	Fuel	Bensiini
Weight (kg) ~	103kg	Garden tools up to	2700 W
Running time at 75% load (h)	20,5h	Protection class	54 IP
Shockproof sockets	2 x 230 V/16 A 1 x CEE 230 V/32 A	Fuel tank capacity [l]	33l
Continuous power	4,0 / 4,0 kVA/kW	Frequency Hz	50 Hz
Kompressorit ja pumput enint.	2000 W	Power 3000 r/min speed kW	4,6 kW
Fuel cons. at 75% PRP [L/h]	1,6l	Power factor (Cos theta)	1 cos φ
Volume	270 cm ³	Alternator model	Duplex
Start-up system	Akkuvasteinen sähkökäynnistys	Sound pressure level LPA (7m) db (A)	64 db(A)
Possible applications	230 V	Sound pressure level LPA db(A)	97 db(A)
Max. Output [LTP] kVA/kW	4,4 / 4,4 kVA/kW	Electric tools up to	3900 W
		Electric devices up to	4000 W
		Welding tools up to	2,5 mm ø

**No. of motor
cylinders and type**

Yksisylinterinen
nelitahtinen

Nominal voltage V

230 V