



1500W Barrel heater for heating water on construction sites

The 1500W fatvärmare is an efficient and reliable solution for heating water in construction site conditions. It is especially suitable for keeping masonry water frost-free during winter and for maintaining water temperature in a barrel.

The heater consists of an acid-resistant steel heating element and a weather-resistant rubber cable. It is easy and safe to use: it must always be connected to a grounded socket, preferably equipped with a 30 mA residual current device (RCD). The IP67 protection class ensures durability even in demanding environments.

When in use, the heating element must always be immersed in water to a depth of at least 40 cm to ensure safe and efficient operation.

The heater has an adjustable thermostat 30°C – 90°C and 0.3 m connecting cable and a plug.

## TEKNISET TIEDOT

|                   |                  |                         |                  |
|-------------------|------------------|-------------------------|------------------|
| <b>Tuotekoodi</b> | 0013001/TS       | <b>Connecting cable</b> | 0,3 m            |
| <b>Power</b>      | 1500 W           | <b>Enclosure class</b>  | IP67             |
| <b>Immersion</b>  | 80 cm (min.40cm) | <b>Weight</b>           | 1,25 kg          |
| <b>Voltage</b>    | 230V             | <b>Measurements</b>     | 87 x 10,5 x 8 cm |
| <b>Thermostat</b> | +30°C – 90°C     |                         |                  |