

MOBILE AIR-TO-AIR HEAT PUMP MWK40 WITH COOLING

The MWK40 air-to-air heat pump combines mobile heating and cooling fully electrically – without fuels, without chillers, without extra adjustment. Fully automatic operation and a CO₂-neutral solution make it a cost-efficient and easy-to-use option for demanding environments.

The unit's operating temperature range extends from -10 °C to +40 °C, so it can be used almost all year round. The MWK40 adjusts the temperature automatically according to a preset target and reacts quickly to changing conditions – without separate resistance heaters or surprises on the electricity bill.

The MWK40 heat pump is an excellent choice for:

- construction sites
- warehouses and production halls
- events and festivals



SKU: 804010003-en

TECHNICAL ATTRIBUTES

Operating temperature	-10°C - +40°C	Supply	32A CEE
Nom. heat output (A7/L35)	42.9 kW	Max. rated current	31 A
COPh (A-7/L35) air	2.24	Enclosure rating	IP44
COPh (A2/L35) air	2.88	Air hose connection	ø 525 mm
COPh (A7/L35) air	3.31	Dimensions (L x W x H)	2.4 x 1.2 x 2.2 m
SCOPh air	2.88	Weight	1020 kg
Airflow	8,000 m ³ /h	Noise level	69 dB(A)

Max. air pressure

200 Pa

Max. condensate

10 l/h

Voltage

400V 50Hz

Refrigerant

R410C

Max. energy consumption

13.9 kW

OTHER PRODUCT IMAGES

