

SIDEFLOW CLEAN 3.5L FOR 400KW HOT WATER SYSTEMS

The **Sideflow Clean 3.5L** is a partial flow filter designed for continuous cleaning of central heating and cooling installations. By connecting a Sideflow Clean to the system, approximately 10% of the main flow (10% PICV) is filtered. Dirt and magnetite are efficiently captured through a combination of a filter bag and magnetic separation.

Sideflow Clean is available in two sizes: **3.5 liters** and **5 liters**.

Key Features:

- Side stream filtration for removing magnetic and non-magnetic suspended solids
- Quick and easy to install and maintain Wall-mounted bracket for simple installation
- Energy-saving insulation layer
- Can be installed for either right-hand or left-hand operation
- Suitable for water and glycol/dosing solutions (max. 50% glycol)

The **Sideflow Clean 3.5L** ensures efficient and reliable system protection by reducing dirt and magnetite build-up, which improves performance and extends the lifetime of heating and cooling systems.



SKU: 17021

TECHNICAL ATTRIBUTES

Käyttöpaine

0,2-10,0
bar

Kvs-arvo

17 m³/h

Järjestelmän enimmäiskoko	70 000 l	Virtauskapasiteetti	2,88 m ³ /h
Virtausnopeus (10 % järjestelmävirtaus)	0,8 l/s	Magneettitankojen määrä	1
		Volume	3,5 l

OTHER PRODUCT IMAGES

