



TSR WH 15 can be used to heat up to 350 m<sup>2</sup> area. The lightweight and corrosion-resistant heater is made of powder-coated galvanized steel. In the design of the heaters, the users' wishes have been carefully considered, e.g. they are easy to maintain and standard filters suitable for heaters. The valves are located pointing upwards.

2 handles and hanging brackets make moving and hanging the heater easy. The heater has a reliable manual interface.

Robust and sturdy TSR WH heaters are manufactured in Finland and all their components are available as spare parts.

Water circulating heaters are suitable for various temporary needs e.g. for new construction and renovation sites.

The heater is connected to the district heating network using a heat exchanger.

## TEKNISET TIEDOT

|                        |                       |                                 |                    |
|------------------------|-----------------------|---------------------------------|--------------------|
| <b>Tuotekoodi</b>      | 1030601015            | <b>Sound level</b>              | 60 dB (A)          |
| <b>Voltage</b>         | 230 V                 | <b>Weight</b>                   | 33,5 kg            |
| <b>Nominal Current</b> | 1,4 A                 | <b>Measurements (H x W x L)</b> | 600 x 395 x 445 mm |
| <b>Heating power</b>   | 15 kW                 | <b>Enclosure class</b>          | IP44               |
| <b>Air current</b>     | 800 m <sup>3</sup> /h | <b>Connectors</b>               | 2 x Camlock 25 mm  |