



The largest heater in our collection, TSR WH50, can be equipped with a durable textile hood, which allows warm air to be evenly 360 ° distributed around the heater over an area of 1000 m<sup>2</sup>. The heater is connected to the district heating network using a heat exchanger.

The lightweight and corrosion-resistant TSR WH 50 heater is made of powder-coated galvanized steel. In the design of the heaters, the wishes of the users have been carefully taken into account, e.g. they are simple to maintain and standard filters are suitable for heaters. The heaters have a reliable manual interface.

Robust and sturdy TSR WH heaters are manufactured in Finland and spare parts availability is good. Heaters have a long life span.

Water circulating heaters are suitable for various temporary needs e.g. for new construction and renovation sites.

TSR WH 50 heater uses standard size textile hood. The hood is not included in the delivery.

## TEKNISET TIEDOT

|                        |                        |                                 |                     |
|------------------------|------------------------|---------------------------------|---------------------|
| <b>Tuotekoodi</b>      | 1030601050             | <b>Sound level</b>              | 90 dB (A)           |
| <b>Voltage</b>         | 400V / 16A             | <b>Weight</b>                   | 152 kg              |
| <b>Nominal Current</b> | 3,0 A                  | <b>Measurements (H x W x L)</b> | 1310 x 755 x 915 mm |
| <b>Heating power</b>   | 50 kW                  | <b>Enclosure class</b>          | IP44                |
| <b>Air current</b>     | 4400 m <sup>3</sup> /h | <b>Connectors</b>               | 2 x Camlock 25 mm   |