

## POWER DISTRIBUTOR TAK 63/125A KS

63 / 125A chainable power distributor with fixed cable supply. In this way, suitable lengths of cable can be measured from between the layers (however, leave a little extra cable in the pole so that the distributor can be moved). The control panel is equipped with interchangeable connectors. The power distributor is made of powder-coated and corrosion-resistant 2 mm aluminum and its robust construction withstands hard handling on site. The power distributor has a carrying handle and can be hung on the wall. The covers are a self-closing security model.

SKU: S19394



### TECHNICAL ATTRIBUTES

<b>Nominal Current</b>	63 A	<b>Weight</b>	14 kg
<b>Nominal voltage</b>	400 V (50 Hz)	<b>Dimensions (H x W x D)</b>	675 x 459 x 196 mm
<b>Input fuse</b>	max. 125 A	<b>Enclosure class</b>	IP44
<b>Socket outlets</b>	8 x 16A (230V), 1 x 16A, 2 x 32A, 1 x 63A	<b>Model</b>	Mini63/8121-12-K
<b>RCD</b>	30 mA ja 300 mA	<b>Ordering number</b>	S19394
<b>Short-circuit resistance</b>	Icf = 17 kA	<b>Approvals</b>	CE

## DIAGRAM IMAGES

