

TSR-MHUB MAIN ELECTRIC CENTRAL 400A

Main electric central in a steel frame made in Finland with high quality European components. Designed with professionals for easy connection and use. Moved easily with a pump cart, forklift or crane. All models have an external housing for measurement.

SKU: 5008995



TECHNICAL ATTRIBUTES

Nominal Current	400A	Weight	250 kg
Nominal voltage	400V	Dimensions (H x W x D)	210cm x 140cm x 100cm
Fuse output	2 x SLK 160, 1 x SLK 400	Enclosure	IP44
Socket outlets	3 x 16A (230V), 2 x 16A, 2 x 32A, 2 x 63A	Model	TSR-MHUB 400A
RCD	2 x 30mA / 2 x 300mA	Approvals	CE
Number of circuit breakers	9	STK num.	34 158 08

DIAGRAM IMAGES

		11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37
D muutos E muutos F muutos	A																	KESKUS	RYHMÄ	OSOITE	TUNNUS	JOHDOTUS	kVA/kW	A / A	HUOM.			
	B																	N/PE EROTUS										
	C																	Q1 PÄÄKYTKIN 400A										
	D																	OF1 SYÖTTÖ, PÄÄVAROKE /400A		AL/CU 35-240mm ²								
	E																	T1-3 VIRTAMUUNTAJAT 400/5A 0,2S										
	F																	OF3 JÄNNITEMITTAUS gC10/25A										
	G																	ERILLINEN kWh-KOTELO KAAPIN KYLJESSÄ										
	H																	OF2 SYÖTTÖ, PÄÄVAROKE /400A		AL/CU 35-240mm ²								
	I																	KESKUKSEN SINEITÖITY OSA										
	J																	F1 /400A	F1	JONVAROKELÄHTÖ /400A		AL/CU 70-240mm ²						
	K																	F2 /160A	F2	JONVAROKELÄHTÖ /160A		AL/CU 10-95mm ²						
	L																	F3 /160A	F3	JONVAROKELÄHTÖ /160A		AL/CU 10-95mm ²						
	M																	JONVAROKE ETUKOJE 100gG /160A	4F	JONVAROKE ETUKOJE 100gG /160A								
	N																											
	O																											
	P																											
	Q																											
R																												
S																												
TSR Group Oy												TSR GROUP OY PÄÄKESKUS 400A VER A PÄÄKAAVIO																
												Kuvittanut: Au /15.4.2020 Piirtäjä: /1/1 Tarkastaja: /1/1																
												Kokonaisuus: SPS/Spooite Työnumero: SÄH PÄÄKAAVIO 400A_VER2																