

TSR-PROLED PLUS 19 000LM

The Proled Plus LED floodlight, which produces a light output of 19,000 lumens, is suitable for use on a construction site, e.g. when attached to a 5m or 10m lamppost, wall, ceiling, pole or crane. The compact 100 watt lamp can illuminate larger outdoor and indoor areas. The opening angle of the light is 120°, i.e. the light opens over a wide area, providing even lighting.

The lamp, which is suitable for indoor and outdoor use, immediately lights up brightly even in freezing temperatures, so it is also suitable for use with a motion detector. Proled Plus floodlights do not produce UV or IR radiation to the wire and they do not contain any mercury or other dangerous substances.

The Proled Plus led lamp has an adjustable folding bracket, from which the lamp can be attached to the ceiling, wall, stand or other surface. The lamp has a 3m connection cable with a plug at the end.

The body of the lamp is made of durable die-cast aluminum and 5 mm tempered glass. If necessary, the glass and its fixing clips are available as a spare part, as well as the connecting cable. High-quality parts from well-known brands such as Philips Lumileds diodes and Meanwell drivers have been used as components in the lamp. Thanks to these components, Proled Plus lamps are very cost-effective considering their high quality.

As a guarantee of quality, we grant a 5-year warranty for Proled Plus lamps.

SKU: 607010002



TECHNICAL ATTRIBUTES

Light output	19 000lm	Color temperature	5000 K
Light source	SDM Philips LED	Protection class	IP44
Connecting cable	3m (shuko)	Service life	50 000 h
Opening angle	120°		

OTHER PRODUCT IMAGES

