

## WATER CIRCUIT HEATER TSR WH30

TSR WH30 can be used to heat up to 600 m<sup>2</sup> area. The lightweight and corrosion-resistant heater is made of powder-coated galvanized steel. In the design of the heaters, the users' wishes have been carefully considered, e.g. they are easy to maintain and standard filters suitable for heaters. The valves are located pointing upwards.

4 wheels, 2 handles and lifting loops make moving the heater easy. The heater has a reliable manual interface.

Robust and sturdy TSR WH heaters are manufactured in Finland and all their components are available as spare parts. A standard size textile hood can be used to distribute air evenly. Hood is not included in the delivery.

Water circulating heaters are suitable for various temporary needs e.g. for new construction and renovation sites.

The heater is connected to the district heating network using a heat exchanger.

SKU: 1030601030



### TECHNICAL ATTRIBUTES

<b>Voltage</b>	230 V	<b>Sound level</b>	65 dB (A)
<b>Nominal Current</b>	2,2 A	<b>Weight</b>	65,5 kg
<b>Heating power</b>	30 kW	<b>Dimensions L x W x H [mm]</b>	1000 x 500 x 650 mm
<b>Air current</b>	2300 m <sup>3</sup> /h	<b>Protection class</b>	IP44
		<b>Connectors</b>	2 x Camlock 25mm

## **ADDITIONAL PRODUCT DESCRIPTION**

## OTHER PRODUCT IMAGES

