

WORKLITE™ MINI 25W 230V SAFETY

Chainable and impact-resistant LED site light with 24-month Guarantee! Made in Finland The WorkLite™ battery-powered safety model ensures lighting even during power failures. It withstands shocks and vibrations. Long-lasting and mechanically highly durable LED as a light source enables cost-effective use even during long projects. WorkLite ™ is easy to install and does not require electrician authorization. This model is available in two voltages: 48 V and 100-230 V. Stock color is red.



SKU: 60009003/MINI

TECHNICAL ATTRIBUTES

Voltage100-230VConnection cable lenght5mPower25WWeight1,3kgLight sourceCOP LED+driverIP-ratingIP44Light output3990lmDimensions (L x W x H)15 x 22,5 x 22,5 x 22,5 cmColor temperature5000KWarranty (years)2Connection cable3×1,5mm2 H07RN-FService life250 000hOperating time with battery4x30min / 2x60min	ILCINICAL	ATTRIBUTES		
Light source COP LED+driver IP-rating IP-44 Light output 3990lm Dimensions (L x W x H) 15 x 22,5 x 22,5 cm Color temperature 5000K Warranty (years) 2 Connection cable 3×1,5mm2 H07RN-F Service life 250 000h Operating time with hattery 4x30min /	Voltage	100-230V	Connection cable lenght	5m
Light output 3990lm Dimensions (L x W x H) 15 x 22,5 x 22,5 cm Color temperature 5000K Warranty (years) 2 Connection cable 3×1,5mm2 H07RN-F Operating time with hattery 4×30min /	Power	25W	Weight	1,3kg
Color temperature 5000K Warranty (years) 22,5cm 2000	Light source	COP LED+driver	IP-rating	IP44
Color temperature 5000K Warranty (years) 2 Connection cable 3×1,5mm2 H07RN-F Service life 250 000h Operating time with hattery 4×30min /	Light output	3990lm	Dimensions (L x W x H)	
Operating time with	Color temperature	5000K	Warranty (years)	·
hattery 4x30min /	Connection cable	3×1,5mm2 H07RN-F	Service life	250 000h