

DEHUMIDIFIER STARING SW30L WITH WIFI - WITHOUT PUMP

The **Staring SW30L WiFi dehumidifier** is a professional unit that removes up to 30 litres of moisture per day (30 °C, RH 80 %). It suits basements, renovation projects, storage rooms and water damage restoration in spaces of up to around 60 square metres.

New: WiFi control via app. The unit can be monitored and adjusted remotely with an app for iOS and Android, so humidity levels, operating settings and runtime can be managed even when you are away from the site. Automatic humidity control reduces unnecessary running and supports energy-efficient use.

The electronic control system allows precise humidity settings together with automatic start and stop, and the unit also has a continuous operation mode. An automatic defrost function and a rotary compressor ensure stable operation in temperatures from 5–35 °C. A durable steel cabinet and an easily removable, washable air filter keep it user-friendly.

The unit has both a **total running hour meter** and a **resettable trip meter**, so you can track total use and use per site.

A **water tank and hose are supplied** with the unit. The 7 litre tank can be emptied by hand, or the dehumidifier can be connected directly to a drain with a hose for continuous operation.

Especially suitable for:

- basements and damp rooms
- small construction projects
- renovation work
- rental applications
- water damage restoration



Note: the unit is not suitable for very aggressive environments such as pig stables.

Download the user manual: [Staring SW series user manual \(PDF\)](#)

TECHNICAL ATTRIBUTES

Kuivausteho	30 L/24h (30 °C RH80%) 20 L/24h (27 °C RH60%)	Refrigerant	R290
Air current	300 m3/h	Operating temperature	5 - 35 °C
Kuivattavan alueen koko	0-60 m2	Kompressorityyppi	Rotary
Voltage	220-240V 50 Hz	Sound level	56 dB
Consumption	420 W	Vesisäiliö	7 l
Weight	29 kg	Ohjaus	WiFi (iOS / Android)
Measurements	472 x 435 x 653 mm	Connecting cable	4,5 m (H07RN-F 3×1,5mm ²)
		CN-koodi	84193900

OTHER PRODUCT IMAGES

