STP3-1500T SUBMERSIBLE PUMP 400 V – THREE-PHASE SITE PUMP

Tuotekortti · 401010022



The **STP3-1500T submersible pump** is a 400 volt three-phase pump for dewatering construction sites. A 1.5 kW motor and a 3″ outlet move up to 700 litres per minute to a head of 14 metres.

PÄÄOMINAISUUDET

- Rated voltage 400 V / 50 Hz, 3-phase
- Motor power 1.5 kW, rated current 3.7 A
- Max. capacity 700 l/min, head 14 m
- Outlet size 3″
- Stainless steel body, strainer for 8 mm particles
- Protection class IP68, submersion depth 25 m
- Cable length 20 m
- Weight 37 kg, sturdy carrying handle

TEKNISET TIEDOT

Tuotekoodi	401010022	**Maximum particle size**	8 mm
Size of cable entry	3"	**Enclosure class**	IP68
Nominal voltage	400V 3~	**Max. submersion depth**	25 m
Engine power	1,5 kW	**Max. liquid temperature**	40°C
Nominal Current	3,7 A	**Connecting cable**	20 m H07RN-F 4G × 1,5 mm² / 400 V 16 A
Maximum flow rate	700 l/min	**Weight**	37 kg
Head	14 m	**Dimensions (H x W)**	559 x 240 mm
Max. pressure	1,4 bar	**CN code**	84137021
Min. pressure	0,2 bar	**EAN code**	5711537069495