

MODULAR SITE DISTRIBUTION BOARD SCS-750

SCS-750 Fastline Modular Site Distribution Board for Flexible Construction Site Power

The **SCS-750 Fastline modular site distribution board** is a versatile **12-module-slot site distribution enclosure** built on the **ABB Fastline system**. It is designed to adapt to changing construction site requirements, allowing the internal configuration to be tailored precisely to each project.

By selecting only the required fuse outlets and components, unnecessary costs can be avoided. When the site changes, the internal setup can be reconfigured to match new demands. Unused module slots are safely covered with protective blank plates, ensuring a clean and secure installation.

The SCS-750 features **Spine readiness**, enabling easy integration of the Spine monitoring system, for example via a Spine main switch module. With Spine, an optional **load indicator light** can be added to visually display the distribution board's load level:

- Green light below 65% load
- Yellow light at 65–85% load
- Red light above 85% load

This visual feedback supports safer operation and helps prevent overload situations on site.

For handling and installation, the enclosure is equipped with **lifting eyes and carrying handles**. The distribution board is supplied as standard with **robust tubular legs**, which can be fully removed and stored inside the enclosure when suspended or during transport. An optional



fixed base is available and is particularly suitable for forklift handling.

Manufactured from **powder-coated aluminum**, the enclosure is corrosion-free and built to withstand harsh construction site conditions. A **lockable door** provides added security.

Manufactured in Finland, the SCS-750 Fastline modular site distribution board delivers durability, flexibility, and high-quality engineering for professional temporary power distribution.

SKU: 505010013

TECHNICAL ATTRIBUTES

Moduulipaikkojen määrä	12	Short-circuit resistance	I _{cf} = 25 kA
Railing	630A	Weight	57 kg
Enclosure class	IP44	Mitat (pakattuna)	750 x 505 x 1060 mm
		Mitat (avattuna)	750 x 705 x 1400 mm

OTHER PRODUCT IMAGES



